


PRICE LIST : 22nd OCTOBER 2021
LP NO. KEI/W&F/LP/21-22/05 DT.22.10.2021
INDUSTRIAL MULTI STRAND CABLES
HSN CODE : 85.44.60.20
KEI HOMECAB - FR PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES - FLAME RETARDANT (FR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

CONDUCTOR (AREA SQ.MM)	NO. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 90M COIL	STANDARD PACKING FOR 90MTR.	RATE PER 180M COIL	STANDARD PACKING FOR 180MTR.	RATE PER MTR
0.50	16/0.20	4	1000	28	2000	12	11.11
0.75	24/0.20	7	1350	28	2700	12	15.00
1.00	32/0.20	11	1770	24	3540	12	19.67
1.50	30/0.25	14	2600	16	5200	8	28.89
2.50	50/0.25	19	4150	12	8300	6	46.11
4.00	56/0.30	26	6140	8	12280	4	68.22
6.00	84/0.30	31	9310	6	18620	3	103.44
10.00	80/0.40	42	16530	1			183.67
16.00	126/0.40	57	25770	1			286.33

KEI CONFLAME - FRLSH PVC INSULATED INDUSTRIAL SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES WITH FLAME RETARDANT LOW SMOKE (FRLSH) PROPERTIES, WITH FLEXIBLE BRIGHT ANNEALED BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

CONDUCTOR (AREA SQ.MM)	NO. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 90M COIL	STANDARD PACKING FOR 90MTR.	RATE PER 180M COIL	STANDARD PACKING FOR 180MTR.	RATE PER MTR
0.50	16/0.20	4	1100	28	2200	12	12.22
0.75	24/0.20	7	1390	28	2780	12	15.44
1.00	32/0.20	11	1860	24	3720	12	20.67
1.50	30/0.25	14	2710	16	5420	8	30.11
2.50	50/0.25	19	4360	12	8720	6	48.44
4.00	56/0.30	26	6430	8	12860	4	71.44
6.00	84/0.30	31	9730	6	19460	3	108.11
10.00	80/0.40	42	17390	1			193.22
16.00	126/0.40	57	27170	1			301.89

KEI BANFIRE - SINGLE CORE, UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - ZERO HALOGEN FLAME RETARDANT (ZHFR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V.

CONDUCTOR (AREA SQ.MM)	NO. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 90M COIL	STANDARD PACKING FOR 90MTR.	RATE PER 180M COIL	STANDARD PACKING FOR 180MTR.	RATE PER MTR
0.75	24/0.20	7	1470	28	2940	12	16.33
1.00	32/0.20	11	1980	24	3960	12	22.00
1.50	30/0.25	14	2840	16	5680	8	31.56
2.50	50/0.25	19	4500	12	9000	6	50.00
4.00	56/0.30	26	6540	8	13080	4	72.67
6.00	84/0.30	31	9890	6	19780	3	109.89
10.00	80/0.40	42	17800	1			197.78
16.00	126/0.40	57	27650	1			307.22

Notes:

- GST and any other tax/levy will be charged extra, at actuals. Freight as per Policy.
- As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.
- Standard colours in Building wires are RED / BLACK / BLUE / YELLOW / GREEN.
- FR / FRLSH & ZHFR wires are supplied in standard lengths of 90M Coils & 180M Coils packed in Master Cartons.
- Please refer to our Marketing Department for Wires & Cables, not covered above.
- For other Colours or Lengths please contact our Marketing Department.
- This Price List is subject to change without prior notice.



KEI INDUSTRIES LIMITED (MUMBAI)

Nirvan Corporate, 7th Floor, Opp. Aghadi Nagar, Andheri Pump House, Andheri - East,
Mumbai - 400 093. Tel. : 022-2837 5642 / 2823 9673 Fax : 2825 8277
uday.sawant@kei-ind.com / swapnil.kanekar@kei-ind.com



PRICE LIST : 22nd OCTOBER 2021

LP NO. KEI/W&F/LP/21-22/05 DT.22.10.2021

PVC INSULATED INDUSTRIAL FLEXIBLE SINGLE & MULTI CORE CABLES

HSN CODE : 85.44.60.20

KEI FLEXIBLE FR PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES FLAME RETARDANT (FR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

(Rate in Rs. Per 100 Mtrs)

SQ.MM	COND. CONST. (NO./DIA. MM)	CURRENT (AMPS) CLIPPED DIRECT TO A SURFACE OR ON A CABLE TRAY, BUNCHED & UNENCLOSED	STD. PACK OF 100 MTR COIL	SINGLE CORE FR	SINGLE CORE HRFR 105 Deg	SINGLE CORE FRLSH	SQ.MM	COND. CONST. (NO./DIA. MM)	CURRENT (AMPS) CLIPPED DIRECT TO A SURFACE OR ON A CABLE TRAY, BUNCHED & UNENCLOSED	SINGLE CORE FR	SINGLE CORE HRFR 105 Deg	SINGLE CORE FRLSH
0.5	16/0.20	4	24	1120	1180	1200	35	276/0.4	110	63260	65380	66340
0.75	24/0.20	7	24	1500	1540	1545	50	396/0.4	145	92040	93390	94180
1.0	32/0.20	12	20	1965	2050	2065	70	354/0.5	200	128980	130850	131830
1.5	30/0.25	16	16	2890	3000	3010	95	484/0.5	235	169880	173330	174620
2.5	50/0.25	22	12	4610	4830	4845	120	608/0.5	270	217250	221100	223990
4.0	56/0.30	29	8	6820	7080	7145	150	750/0.5	310	272240	277140	279220
6	84/0.30	37	4	10345	10790	10810	185	925/0.5	360	329960	336490	339290
10	80/0.40	51	1	18370	19050	19320	240	1210/0.5	425	435560	443750	448140
16	126/0.40	68	1	28630	30020	30190	300	1527/0.5	490	542840	552660	558540
25	196/0.40	86	1	45290	46830	47500	400	2036/0.5	590	718630	720830	727400

KEI FLEXIBLE PVC INSULATED MULTICORE FR PVC SHEATHED MULTISTRANDED CABLES WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

SQ.MM	COND. CONST. (NO./DIA.MM)	2 CORE	3 CORE	4 CORE	5 CORE	6 CORE	7 CORE	10 CORE	12 CORE	14 CORE	16 CORE	19 CORE	24 CORE
0.5	16/0.20	3360	4440	5510	7490	8680	9470	14700	16970	19360	22090	25510	32630
0.75	24/0.20	4560	5820	7490	10330	11790	13020	19790	22990	26550	30260	35140	44880
1.0	32/0.20	5070	6930	9100	12040	14300	16050	24310	28110	32480	37060	42940	54750
1.5	30/0.25	6930	9670	12500	16810	19680	22070	32820	38610	44720	51060	59330	75930
2.5	50/0.25	11240	15570	20400	26650	31510	35180	51970	61530	71950	81710	95650	122130
4.0	56/0.3	17510	25320	32590	43740	50110	58050	85410	101280	117470	133640	156960	201710
6	84/0.3	25800	36680	48920	62980								
10	80/0.4	43150	61930	81720	106640								
16	126/0.4	66450	95200	125660									
25	196/0.4		153960	202090									
35	276/0.4		214080	279180									
50	396/0.4		306580	400770									
70	354/0.5		423050	556660									
95	484/0.5		0	736530									
120	608/0.5												

Note :

KEI 3 CORE FLAT CABLES FOR SUBMERSIBLE PUMP MOTORS

(Rate in Rs. Per 100 Mtrs)

SQ. MM	COND. CONST. (NO./DIA.MM)	RATE
1.5	30/0.25	10050
2.5	50/0.25	15540
4	56/0.3	23440
6	84/0.3	35060
10	80/0.4	57910
16	126/0.4	91510
25	196/0.4	138210

- FRLS Loading - 3% Extra for Multi Core Flexible Cables.**
- KEI 3 Core Flat Submersible Cables PVC Insulated & Sheathed with XLPE can be supplied at the same rates as PVC insulated cables.
- Packing for 3 Core Flat Submersible Cables :**
 - Cables upto 4sqmm are supplied in 500Mtr/1000Mtr drums.
 - Cables from 6sqmm to 25sqmm are supplied in 500Mtr drums.
 - Cables of 1.5sqmm, 2.5sqmm & 4sqmm are also supplied in 300Mtr coil.
- Packing for Single & Multi Core Round Wire Flexible cables :**
 - Single Core Flexible cables upto 6sqmm are supplied in Master Carton as shown above.
 - Single Core 10sqmm and above will be supplied in single coil packing.
 - Single Core 120sqmm and above & Multicore 6sqmm & above available in coil packing.

- GST and any other tax/levy will be charged extra, at actuals. Freight as per Policy.
- Please refer to our Marketing Department for Wires & Cables, not covered above.
- This Price List is subject to change without prior notice.